# HCS-5100R Digital Infrared Receivers



# **Features**

- Compliant to IEC 61603-7 and IEC 60914
- Compatible with any other IR simultaneous interpretation system compliant to IEC 61603-7
- Independent intellectual property chipset for digital infrared processor, and DQPSK digital modulation/demodulation technology
- Transmitting in 2~8 MHz frequency band eliminates disturbance from high frequency lighting systems
- Channel selection via up/down button, at most 4,8,16 or 32 channels available
- Back-lighting LCD display with channel number, language name, battery and signal status indication
- Number of available channels is always the same as the number of channels in use by the system, eliminating the need to scroll through unused channels
- Adjustable volume
- Unique 270° super wide reception angle, ensuring perfect sound quality even when casually placed
- Audio signal automatically muted when signal is too low, ensuring that the user receives only high quality audio
- Ergonomically compact and elegant design
- Lightweight and handy receiver in conjunction with single earphone (EP-820AS/EP-828/EP-829SW) or headphone (HCS-5100PA /HCS-5100PB) for easy and comfortable use
- Can be hung over the neck via a nice strap or fit into the shirt pocket
- Freedom of movement within the range of IR power radiator
- No limit to the receiver number within the IR power radiation range
- Works without errors, even in bright sunlight
- Built-in high precision rechargeable circuitry to prolong battery life
- Can be used with disposable batteries (2×AA alkaline batteries, not included) or environmentally-friendly Ni-MH rechargeable battery pack (not included)
- No power consumption when headphone is disconnected
- Measurement mode for easy checking of radiator coverage
- Can be equipped with alarm system to prevent loss
- Can work with HCS-5300 digital infrared wireless conference system and achieve up to 1+3 channels infrared wireless simultaneous interpretation

HCS-5100R is a series of IR receivers, which can receive up to 32 language channels. Both rechargeable Ni-MH battery and disposable battery can be used. The receiver is equipped with channel selector, volume control, power switch,  $\varnothing$  3.5 mm stereo earphone jack, and charging circuit on the PCB. A LCD displays channel number with language name, received signal intensity, battery capacity and volume.

# **Controls and Indicators**

- LCD displays channel number, language name, battery capacity, signal intensity and volume
- Power switch
- Channel selector buttons
- Volume control buttons

#### Interconnections

- Ø 3.5 mm stereo earphone jack
- Charging contacts

# **Technical Specifications**

# System Specifications

Modulation	DQPSK, according to IEC 61603-7
Modulation frequency	
Carriers 0 to 5	2 to 6 MHz, according to IEC 61603-7
Carriers 6 and 7	up to 8 MHz
Frequency response	20 Hz to 10 kHz (-3dB) at standard quality;
	20 Hz to 20 kHz (-3dB) at perfect quality
THD at 1 KHz	<0.05%
Isolation	>80 dB
Dynamic range	>80 dB
Weighted SNR	>80 dBA
	-12 dBV ~ +12 dBV (adjustable)

# **Electrical**

IR irradiance level	4 mW/m <sup>2</sup> per carrier
Angle of sensitivity	270°
Headphone output level at 2.4 V	450 mVrms (speech at maximum
	volume, 32 Ohm headphone)
Headphone output freq. range	20 Hz to 20 kHz
Headphone output impedance	32 Ohm to 2 kOhm
Max. SNR	>80 dBA
Supply voltage	1.8 V to 3.6 V, nominal 2.4 V
Power consumption	
Normal (at 2.4 V)	38 mA (32 Ohm headphone)
Headphone jack unplugged	0 mA
Battery life	
2×AA alkaline cells	70 hours
Rechargeable battery pack	42 hours



# **Mechanical**

Dimensions h x w x d (mm)	155 × 46 × 24
Weight	
Excl. batteries	80 g
	135 g
Color	Black (PANTONE 419 C)
	White (PANTONE Cool Gray 1 C)

00101	White (PANTONE Cool Gray 1 C)
Ordering Information	
HCS-5100R/04	4 CHs Digital Infrared Receiver (LCD, language display, optional rechargeable battery pack or 2xAA alkaline cells, excl. battery, black)
HCS-5100R/08	8 CHs Digital Infrared Receiver (LCD, language display, optional rechargeable battery pack or 2xAA alkaline cells, excl. battery, black)
HCS-5100R/16	16 CHs Digital Infrared Receiver (LCD, language display, optional rechargeable battery pack or 2xAA alkaline cells, excl. battery, black)
HCS-5100R/32	32 CHs Digital Infrared Receiver (LCD, language display, optional rechargeable battery pack or 2xAA alkaline cells, excl. battery, black)
HCS-5100R_W/04	4 CHs Digital Infrared Receiver (LCD, language display, optional rechargeable battery pack or 2xAA alkaline cells, excl. battery, white)
HCS-5100R_W/08	8 CHs Digital Infrared Receiver (LCD, language display, optional rechargeable battery pack or 2xAA alkaline cells, excl. battery, white)
HCS-5100R_W/16	16 CHs Digital Infrared Receiver (LCD, language display, optional rechargeable battery pack or 2xAA alkaline cells, excl. battery, white)
HCS-5100R_W/32	32 CHs Digital Infrared Receiver (LCD, language display, optional rechargeable battery pack or 2xAA alkaline cells, excl. battery, white)

# HCS-5100RA Digital Infrared Receivers



#### **Features**

- Compliant to IEC 61603-7 and IEC 60914
- Compatible with any other IR simultaneous interpretation system compliant to IEC 61603-7
- Independent intellectual property chipset for digital infrared processor, and DQPSK digital modulation/demodulation technology
- Transmitting in 2~8 MHz frequency band eliminates disturbance from high frequency lighting systems
- Channel selection via up/down button, at most 4,8,16 or 32 channels available
- Back-lighting LCD display with channel number, language name, battery and signal status indication
- Number of available channels is always the same as the number of channels in use by the system, eliminating the need to scroll through unused channels
- Adjustable volume
- Unique 270° super wide reception angle, ensuring perfect sound quality even when casually placed
- Audio signal automatically muted when signal is too low, ensuring that the user receives only high quality audio
- Ergonomically compact and elegant design
- Lightweight and handy receiver in conjunction with single earphone (EP-820AS/EP-828/EP-829SW) or headphone (HCS-5100PA/HCS-5100PB) for easy and comfortable use
- Can be hung over the neck via a nice strap or fit into the shirt pocket
- Freedom of movement within the range of IR power radiator
- No limit to the receiver number within the IR power radiation range
- Works without errors, even in bright sunlight
- Used with disposable batteries (2×AA alkaline batteries, not included)
- No power consumption when headphone is disconnected
- Measurement mode for easy checking of radiator coverage
- Can be equipped with alarm system to prevent loss
- Can work with HCS-5300 digital infrared wireless conference system and achieve up to 1+3 channels infrared wireless simultaneous interpretation

HCS-5100RA is a series of IR receivers, which can receive up to 32 language channels, only for disposable battery. The receiver is equipped with channel selector, volume control, power switch,  $\varnothing$  3.5 mm stereo earphone jack. A LCD displays channel number with language name, received signal intensity, battery capacity and volume.

# **Controls and Indicators**

- LCD displays channel number, language name, battery capacity, signal intensity and volume
- Power switch
- Channel selector buttons
- Volume control buttons

# Interconnections

■ Ø 3.5 mm stereo earphone jack

# **Technical Specifications**

# System Specifications

Modulation	DQPSK, according to IEC 61603-7
Modulation frequency	
Carriers 0 to 5	2 to 6 MHz, according to IEC 61603-7
Carriers 6 and 7	up to 8 MHz
Frequency response	20 Hz to 10 kHz (-3dB) at standard quality;
	20 Hz to 20 kHz (-3dB) at perfect quality
THD at 1 KHz	<0.05%
Isolation	>80 dB
Dynamic range	>80 dB
Weighted SNR	>80 dBA
	-12 dBV ~ +12 dBV (adjustable)

# **Electrical**

IR irradiance level	4 mW/m² per carrier
Angle of sensitivity	270°
Headphone output level at 2.4 V	450 mVrms (speech at maximum
	volume, 32 Ohm headphone)
Headphone output freq. range	20 Hz to 20 kHz
Headphone output impedance	32 Ohm to 2 kOhm
Max. SNR	>80 dBA
Supply voltage	1.8 V to 3.6 V, nominal 2.4 V
Power consumption	
Normal (at 2.4 V)	38 mA (32 Ohm headphone)
Headphone jack unplugged	0 mA
Battery life	70 hours

# **Mechanical**

Dimensions h x w x d (mm)	155 × 46 × 24
Weight	
Excl. batteries	80 g
Incl. batteries	135 g
Color	Black (PANTONE 419 C)
	White (PANTONE Cool Gray 1 C)

# **Ordering Information** HCS-5100RA/04 4 CHs Digital Infrared Receiver (LCD, language display, 2xAA alkaline cells, black) HCS-5100RA/08 8 CHs Digital Infrared Receiver (LCD, language display, 2xAA alkaline cells, black) HCS-5100RA/16 16 CHs Digital Infrared Receiver (LCD, language display, 2xAA alkaline cells, black) HCS-5100RA/32\_\_\_\_\_\_32 CHs Digital Infrared Receiver (LCD, language display, 2xAA alkaline cells, black) HCS-5100RA\_W/04 4 CHs Digital Infrared Receiver (LCD, language display, 2xAA alkaline cells, white)

alkaline cells, white)

(LCD, language display, 2xAA

(LCD, language display, 2xAA alkaline cells, white)

HCS-5100RA\_W/32\_\_\_\_\_\_32 CHs Digital Infrared Receiver (LCD, language display, 2xAA alkaline cells, white)

HCS-5100RA\_W/08\_\_\_\_\_\_8 CHs Digital Infrared Receiver